

INDUSTRIAL COMPONENT DATA

EMUG 22- 4REL/KSR-G 24/ 1AU 2942399 PHOENIX CONTACT

Multiple relay module

Brand: PHOENIX CONTACT | Manufacturer Part Number: EMUG 22-4REL/KSR-G 24/ 1AU



Manufacturer	PHOENIX CONTACT
MPN / Reference	EMUG 22-4REL/KSR-G 24/ 1AU
Catalog number	2942399
Category	Switching relay
Minimum order	5 Pcs
Document ID	EO-9E8DA3F376
Generated	2026-08-03

Product Overview

Multiple relay module

Multi-channel relay module with 4 soldered mini-switching relays for DC voltage with light indication and 1 open contact each, contact for small to large powers, input voltage 24 V DC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Relays
--------------	-------------------------------------

Additional Product Information

Key Commercial Data

Orderkey 2942399

Packing unit 5 pc

Note Made to Order (non-returnable)

GTIN 4017918080716

Weight per Piece (excluding packing) 85.780 g

Custom tariff number 85364190

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 22.5 mm

Height 60 mm

Depth 79 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 55 °C

Coil side

Nominal input voltage UN 24 V DC

Input voltage range in reference to UN 0.8 ... 1.1

Typical input current at UN 12 mA

Typical response time 7 ms

Typical release time 8 ms

Protective circuit Damping diode, polarity protection Damping diode, polarity protection diode, bridge rectifier at AC input

Operating voltage display yes

Power dissipation for nominal condition 0.29 W

Contact side

Contact type Single contact, 1 N/O contact

Type of switch contact Single contact

Contact material Fine grained silver (AgNi 0,15), 5 µm hard gold-plated

Maximum switching voltage 60 V AC/DC

Maximum inrush current 0.2 A

Limiting continuous current 2 A

Interrupting rating (ohmic load) max. 5 W (at 24 V DC)

10 W (at 48 V DC)

12 W (at 60 V DC)

12 VA (for 60 V AC)

General

Test voltage relay winding/relay contact 2.5 kV AC (50 Hz, 1 min.)

Operating mode 100% operating factor

Mechanical service life approx. 2x 10⁷ cycles

Mounting position any

Assembly instructions In rows with zero spacing

Net weight (SAP) 85.78 g

Standards and Regulations

Standards/regulations IEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EMUG 22-4REL/KSR-G 24/ 1AU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.