


INDUSTRIAL COMPONENT DATA

E/UK 1201442 PHOENIX CONTACT End clamp

Brand: PHOENIX CONTACT | Manufacturer Part Number: E/UK



Manufacturer	PHOENIX CONTACT
MPN / Reference	E/UK
Catalog number	1201442
Category	End bracket for terminal block
Minimum order	50 Pcs
Document ID	EO-958B099FB1
Generated	2026-08-01

Product Overview

End clamp

End support, material:PA, color:gray, Rail mounting NS 32 or NS 35

End bracket, Mounting on a DIN rail NS 32 or NS 35, material: PA, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type End bracket

Data management status

Article revision 06

Connection dataTightening torque ... 0.8 Nm

DimensionsDimensional drawing

Width 9.5 mm

Height 50.5 mm

Depth 35.3 mm

Depth on NS 35/7,5 36.8 mm

Length 50.5 mm

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Relative insulation material temperature index (Elec., UL 746 B) 125 °C

Environmental and real-life conditions Ambient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

Mounting Mounting type NS 35/7,5

NS 35/15

NS 32

ETIM for 1201442 Terminal blocks (EC001041)

Feature Name

Feature Value

Colour (EF000007)

Grey

Mounting method (EF000003)

DIN rail (top hat rail) 35 mm

Type of latching (EF002667)

Screw fix

Material (EF002169)

Other

Material quality (EF001257)

Polyamide (PA)

Inflammability class of insulation material according to UL94 (EF002521)

V0

Height (EF000040)

50.5 mm

Depth (EF000049)

35.3 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / E/UK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.