

INDUSTRIAL COMPONENT DATA**D-PT 2,5-TWIN-MT 3211317 PHOENIX CONTACT End cover**

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-PT 2,5-TWIN-MT



Manufacturer	PHOENIX CONTACT
MPN / Reference	D-PT 2,5-TWIN-MT
Catalog number	3211317
Category	Endplate and partition plate for terminal block
Minimum order	50 Pcs
Document ID	EO-A3AB1F4A67
Generated	2026-08-03

Product Overview

End cover

End cap, length: 73.7 mm, width: 2.2 mm, height: 29.1 mm, colour: grey

End cover, depth: 29.1 mm, width: 2.2 mm, height: 73.7 mm, color: gray

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > Modular TBs****Additional Product Information**

Technical dataProduct propertiesProduct type End cover

Data management status

Article revision 02

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

Material specificationsColor gray (RAL 7042)

Material PA

Flammability rating according to UL 94 V0

Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
DimensionsWidth 2.2 mm
End cover width 2.2 mm
Height 73.7 mm
Depth 29.1 mm
Depth on NS 3...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / D-PT 2,5-TWIN-MT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.