

**INDUSTRIAL COMPONENT DATA****D-PTME 6/1P 3212307 PHOENIX CONTACT End cover**

Brand: PHOENIX CONTACT | Manufacturer Part Number: D-PTME 6/1P



|                 |                                                 |
|-----------------|-------------------------------------------------|
| Manufacturer    | PHOENIX CONTACT                                 |
| MPN / Reference | D-PTME 6/1P                                     |
| Catalog number  | 3212307                                         |
| Category        | Endplate and partition plate for terminal block |
| Minimum order   | 10 Pcs                                          |
| Document ID     | EO-2250A52316                                   |
| Generated       | 2026-08-01                                      |

**Product Overview**

End cover

End cap, length: 99.4 mm, width: 2.2 mm, height: 41.9 mm, colour: grey

End cap, depth: 41.9 mm, width: 2.2 mm, height: 99.4 mm, colour: grey

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **PHOENIX CONTACT > Modular TBs****Additional Product Information**

Key Commercial Data

Orderkey 3212307

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 303 (C-1-2017)

GTIN 4046356623223

Weight per Piece (excluding packing) 4.700 g

Custom tariff number 85389099

Country of origin DE (Germany)

General

Color gray

Material PA

Flammability rating according to UL 94 V0

**Dimensions**

Width 2.2 mm

End cover width 2.2 mm

Length 99.4 mm

Height 41.9 mm

Height NS 35/7,5 49.6 mm

Height NS 35/15 57.1 mm

**General**

Relative insulation material temperature index (Elec., UL 746 B) 130 °C

Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 125 °C

Static insulating material application in cold -60 °C

Behavior in fire for rail vehicles (DIN 5510-2) Test passed

Flame test method (DIN EN 60695-11-10) V0

Oxygen index (DIN EN ISO 4589-2) &gt;32 %

NF F16-101, NF F10-102 Class I 2

NF F16-101, NF F10-102 Class F 2

Surface flammability NFPA 130 (ASTM E 162) passed

Specific optical density of smoke NFPA 130 (ASTM E 662) passed

Smoke gas toxicity NFPA 130 (SMP 800C) passed

Calorimetric heat release NFPA 130 (ASTM E 1354) 27,5 MJ/kg

Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3

Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3

**Standards and Regulations**

Flammability rating according to UL 94 V0

Fire protection for rail vehicles (DIN EN 4554...

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / D-PTME 6/1P with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.