

INDUSTRIAL COMPONENT DATA

WP-EC TPE HF 10,0 BK 3240974 PHOENIX CONTACT

Transition sleeve from hose to cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: WP-EC TPE HF 10,0 BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	WP-EC TPE HF 10,0 BK
Catalog number	3240974
Category	Terminal sleeve for protective hose
Minimum order	50 Pcs
Document ID	EO-7E03DC94A6
Generated	2026-08-01

Product Overview

Transition sleeve from hose to cable

Tube to cable connection sleeve, material: TPE, color: black, flammability class according to UL94: HB

Transition sleeve from hose to cable, material: TPE, color: black, flammability rating in acc. with UL 94: HB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Industrial plug-in connectors/interfaces

Additional Product Information

Technical dataProduct propertiesProduct type Protective cap

Data management status

Article revision 00

DimensionsLength 29 mm

Diameter 10 mm

Material specificationsMaterial TPE

Flammability rating according to UL 94 HB

Components halogen-free

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -40 °C ... 120 °C

Short-term temperature 150 °C

ETIM for 3240974 Flexible conduit systems (EC000519)

Feature Name

Feature Value

Nominal size in inch (EF005462)

Other

Material quality (EF001257)

Other

Closed end cap (EF003654)

No

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / WP-EC TPE HF 10,0 BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.