

INDUSTRIAL COMPONENT DATA

EO-AB/PT/S/15 0804173 PHOENIX CONTACT Socket, Pin connector pattern type AB 15A, Push-in spring connection, ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-AB/PT/S/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-AB/PT/S/15
Catalog number	0804173
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-74426DF611
Generated	2026-08-03

Product Overview

Socket, Pin connector pattern type AB 15A, Push-in spring connection, for USA and other countries, switch, gray, for mounting on a DIN rail in the service interface or direct mounting, 125 V AC, 15 A, -20 °C, 60 °C, UL 508

Power Outlet, Plug-in Face Type AB 15A, Push-In Spring Connection, for USA and Other Countries, Switch, Grey, For Rail Mounting at Service Interface or Direct Mounting, 125 VAC, 15 A, -20 °C, 60 °C, UL 508

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804173

Packing unit 1 pc

Minimum order quantity 5 pc

Catalog page Page 563 (C-3-2019)

GTIN 4055626226941

Weight per Piece (excluding packing) 92.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Drawings

Ambient conditions

Connection data

[Environmental Product Compliance](#)

[Dimensions](#)

[General](#)

[Standards and Regulations](#)

[Classifications](#)

[Drawings](#)

[Circuit diagram](#)

[Back to top](#)[Dimensions](#)

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)[General](#)

Nominal voltage UN 125 V AC (60 Hz)

Nominal current IN 15 A

Status display No

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations UL 508

Country ID USA

[Back to top](#)[Connection data](#)

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Push-in spring connection

[Back to top](#)[Standards and Regulations](#)

Standards/regulations UL 508

Flammability rating according to UL 94 V0

[Back to top](#)[Environmental Product Compliance](#)

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)[Classifications](#)

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-AB/PT/S/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.