

INDUSTRIAL COMPONENT DATA

EO-AB/UT/15 0804152 PHOENIX CONTACT Socket, Pin connector pattern type AB 15A, Screw connection, for USA and..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-AB/UT/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-AB/UT/15
Catalog number	0804152
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-A89277D5F4
Generated	2026-07-29

Product Overview

Socket, Pin connector pattern type AB 15A, Screw connection, for USA and other countries, gray, for mounting on a DIN rail in the service interface or direct mounting, 125 V AC, 15 A, -20 °C, 60 °C, UL 508

Power Outlet, Type AB 15A Plug-in Face, Screw Connection, for U.S. and Other Countries, Gray, for Rail Mounting at Service Interface or Direct Mounting, 125 VAC, 15 A, -20 °C, 60 °C, UL 508

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0804152

Packing unit 1 pc

Minimum order quantity 5 pc

Catalog page Page 563 (C-3-2019)

GTIN 4055626226767

Weight per Piece (excluding packing) 84.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Drawings

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

General

Standards and Regulations

Classifications

Drawings

Circuit diagram

Back to topDimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

Back to topAmbient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Back to topGeneral

Nominal voltage UN 125 V AC (60 Hz)

Nominal current IN 15 A

Status display No

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations UL 508

Country ID USA

Back to topConnection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

Back to topStandards and Regulations

Standards/regulations UL 508

Flammability rating according to UL 94 V0

Back to topEnvironmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-AB/UT/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.