

INDUSTRIAL COMPONENT DATA

EO-AB/UT/LED/S/15 0804160 PHOENIX CONTACT Socket, Pin connector pattern type AB 15A, Screw connection, for U..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-AB/UT/LED/S/15



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-AB/UT/LED/S/15
Catalog number	0804160
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-7583738A22
Generated	2026-08-01

Product Overview

Socket, Pin connector pattern type AB 15A, Screw connection, for USA and other countries, with LED display and switch, gray, for mounting on a DIN rail in the service interface or direct mounting, 125 V AC, 15 A, -20 °C, 60 °C, UL 508

Power socket, Plug-in face type AB 15A, Screw connection, for the USA and other countries, with light indication and switch, grey, for rail mounting at the service interface or direct mounting, 125 VAC, 15 A, -20 °C, 60 °C, UL 508

Socket, Pin connector pattern type AB 15A, for USA and other countries, with LED display and switch, gray, DIN rail or direct mounting, -5 °C, 40 °C, UL 508

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Socket

Country ID USA

Data management status

Article revision 03

Connection dataScrew thread M3

Tightening torque 0.5 ... 0.6 Nm

Stripping length 8 mm

Internal cylindrical gage A3

B3

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)
Conductor cross section flexible 0.25 mm² ... 2.5 mm²
Conductor cross section, flexible [AWG] 24 ... 14 (converted acc. to IEC)
Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 2.5 mm²
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) 0.2 mm² ... 4 mm²
Nominal current 15 A
Nominal voltage 125 V AC (60 Hz)
SignalingStatus display yes
DimensionsWidth 45 mm
Height 75 mm
Depth 75 mm
Material specificationsColor gray (RAL 7042)
Flammability rating according to UL 94 V0
Insulating material PA
Contact material CuZn37
Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Surf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-AB/UT/LED/S/15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.