

INDUSTRIAL COMPONENT DATA

EO-CF/PT/YE 1068067 PHOENIX CONTACT Socket, Pin connector pattern type CF, yellow, for mounting on a DIN rail.

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-CF/PT/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-CF/PT/YE
Catalog number	1068067
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-52F026CE49
Generated	2026-08-01

Product Overview

Socket, Pin connector pattern type CF, yellow, for mounting on a DIN rail in the service interface or direct mounting, -20 °C, 60 °C, VDE 0620-1

Power socket, Plug-in face type CF, yellow, for rail mounting at the service interface or direct mounting, -20 °C, 60 °C, VDE0620-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1068067

Packing unit 1

Catalog page Page 562 (C-3-2019)

GTIN 4055626739656

Custom tariff number 85366990

Drawings

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

General

Standards and Regulations

Classifications

Drawings

Dimensional drawing

Back to topDimensions

Width 45 mm

Height 75 mm

Depth 60 mm

Back to topAmbient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Back to topGeneral

Status display No

Contact material CuZn37

Color yellow

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations VDE 0620-1

Country ID Germany

Back to topConnection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Back to topStandards and Regulations

Standards/regulations VDE 0620-1

Flammability rating according to UL 94 V0

Back to topEnvironmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCI@ss

eCI@ss 5.1 27142300

eCI@ss 6.0 27142300

eCI@ss 7.0 27142305

eCI@ss 8.0 27142305

eCI@ss 9.0 27142305

Back to topETIM

ETIM 5.0 EC001663

ETIM 6.0 EC001663

ETIM 7.0 EC001663

Back to top

ETIM for 1068067 Modular devices for distribution board/surface mounting (EC001663)

Feature Name

Featur...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-CF/PT/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.