

INDUSTRIAL COMPONENT DATA

EO-CF/UT/LED/F/YE 1068030 PHOENIX CONTACT Socket, Pin connector pattern type CF, LED display and fuse 5 x 20..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-CF/UT/LED/F/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-CF/UT/LED/F/YE
Catalog number	1068030
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-639A67FCC9
Generated	2026-08-02

Product Overview

Socket, Pin connector pattern type CF, LED display and fuse 5 x 20 mm, 6.3 A, yellow, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, VDE 0620-1

Power socket, Plug-in face type CF, 5 x 20 mm indicator light and fuse, 6.3 A, yellow, for rail mounting at the service interface or direct mounting, 250 VAC, 6 A, -20 °C, 60 °C, VDE0620-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 1068030

Packing unit 1

Catalog page Page 562 (C-3-2019)

GTIN 4055626739571

Custom tariff number 85366990

Drawings

Ambient conditions

Standards and Regulations

Dimensions

General

Classifications

Drawings

Circuit diagram

Back to topDimensions

Width 45 mm

Height 75 mm

Depth 60 mm

Back to topAmbient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Back to topGeneral

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display Yes

Contact material CuZn37

Color yellow

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations VDE 0620-1

Country ID Germany

Fuse 6.3 A (exchangeable)

Back to topStandards and Regulations

Standards/regulations VDE 0620-1

Flammability rating according to UL 94 V0

Back to topClassifications

eCl@ss

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7.0 27142305

eCl@ss 8.0 27142305

eCl@ss 9.0 27142305

Back to topETIM

ETIM 5.0 EC001663

ETIM 6.0 EC001663

ETIM 7.0 EC001663

Back to top

ETIM for 1068030 Modular devices for distribution board/surface mounting (EC001663)

Feature Name

Feature Value

Rated voltage (EF000228)

250 V

Rated current (EF000227)

6.3 A

With hinged lid (EF000117)

No

With enhanced contact protection (EF000389)

No

With control lamp (EF005055)

Yes

Width in number of modular spacings (EF002950)

2.5

Built-in depth (EF000218)

62.1 mm

Degree of protection (IP) (EF005474)

IP20

Number of socket outlets (EF000336)

1

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-CF/UT/LED/F/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.