

INDUSTRIAL COMPONENT DATA

EO-CF/UT/YE 1068038 PHOENIX CONTACT Socket, Pin connector pattern type CF, yellow, for mounting on a DIN rail..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-CF/UT/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-CF/UT/YE
Catalog number	1068038
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-EFA2FF9BE4
Generated	2026-07-31

Product Overview

Socket, Pin connector pattern type CF, yellow, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, VDE 0620-1

Power socket, Plug-in face type CF, yellow, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, VDE0620-1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 1068038

Packing unit 1 pc

Minimum order quantity 5 pc

Catalog page Page 562 (C-3-2019)

GTIN 4055626739823

Weight per Piece (excluding packing) 72.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Drawings

Ambient conditions

Connection data

[Classifications](#)

[Dimensions](#)

[General](#)

[Standards and Regulations](#)

[Drawings](#)

[Dimensional drawing](#)

[Circuit diagram](#)

[Back to top](#)[Dimensions](#)

Width 45 mm

Height 75 mm

Depth 60 mm

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)[General](#)

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display No

Contact material CuZn37

Color yellow

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations VDE 0620-1

Country ID Germany

[Back to top](#)[Connection data](#)

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

[Back to top](#)[Standards and Regulations](#)

Standards/regulations VDE 0620-1

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCI@ss

eCI@ss 8.0 27142305

eCI@ss 9.0 27142305

[Back to top](#)[ETIM](#)

ETIM 5.0 EC001663

ETIM 6.0 EC001663

ETIM 7.0 EC001663

[Back to top](#)

ETIM for 1068038 Modular devices for distribution board/surface mounting (EC001663)

Feature Name

Feature Value

Rated voltage (EF000228)

250 V

Rated current (EF000227)

16 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-CF/UT/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.