

INDUSTRIAL COMPONENT DATA

EO-D/PT/LED/DUO/GN 0804014 PHOENIX CONTACT Double socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-D/PT/LED/DUO/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-D/PT/LED/DUO/GN
Catalog number	0804014
Category	Socket outlet for distribution board
Minimum order	2 Pcs
Document ID	EO-FB12CCC189
Generated	2026-08-01

Product Overview

Double socket

Double power socket, Reference: D, Push-in spring connection, for India/Africa and other countries, with light indication, NOT suitable for South Africa (ZA), green, for rail mounting at the service interface or direct mounting, 250 VAC, 6 A, -20 °C, 60 °C, IS1293

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804014

Packing unit 2 pc

Minimum order quantity 2 pc

Note Made to Order (non-returnable)

Catalog page Page 607 (C-3-2017)

GTIN 4055626225579

Weight per Piece (excluding packing) 133.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Width 90 mm

Height 75 mm

Depth 57.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 6 A

Status display Yes

Contact material CuZn37

Color green

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations IS 1293

Country ID India / Africa

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Push-in spring connection

Standards and Regulations

Standards/regulations IS 1293

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Classifications

eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss 7.027142305eCl@ss 8.027142305eCl@ss 9.027142305

ETIM 5.0EC001663ETIM 6.0EC001663

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-D/PT/LED/DUO/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.