

INDUSTRIAL COMPONENT DATA

EO-D/UT/F/GN 0804006 PHOENIX CONTACT Socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-D/UT/F/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-D/UT/F/GN
Catalog number	0804006
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-C65004464D
Generated	2026-07-29

Product Overview

Socket

Power socket, Reference: D, Screw connection, for India/Africa and other countries, integrated fuse, NOT suitable for South Africa (ZA), green, for rail mounting at the service interface or direct mounting, 250 VAC, 6 A, -20 °C, 60 °C, IS1293

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0804006

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 607 (C-3-2017)

GTIN 4055626224695

Weight per Piece (excluding packing) 80.300 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 6 A

Status display No

Contact material CuZn37

Color green

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations IS 1293

Country ID India / Africa

Connection dataConductor cross section solid min. 0.2 mm²Conductor cross section solid max. 4 mm²Conductor cross section flexible min. 0.2 mm²Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

Standards and Regulations

Standards/regulations IS 1293

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

ClassificationseCl@ss 4.027140815eCl@ss 4.127140815eCl@ss 5.027143423eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss
7.027142305eCl@ss 8.027142305eCl@ss 9.027142305

ETIM 2.0EC001121ETIM 3.0EC000125ETIM 4.0EC000125ETIM 5.0EC001663ETIM 6.0EC001663

UNSPSC 6.0131261501UNSPSC 7.090131261501UNSPSC 1131261501UNSPSC 12.013126150...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend PHOENIX CONTACT / EO-D/UT/F/GN with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.**GLOBAL OFFICES**Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, DubaiCatalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.