

INDUSTRIAL COMPONENT DATA

EO-E/PT/SH/GN 0804021 PHOENIX CONTACT Socket, Pin connector pattern type E, Push-in spring connection, for F..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-E/PT/SH/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-E/PT/SH/GN
Catalog number	0804021
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-1488056272
Generated	2026-08-01

Product Overview

Socket, Pin connector pattern type E, Push-in spring connection, for France and other countries, with extended touch proofness/shutter, green, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, NF C61-314

Power socket, Type E plug-in face, Push-in spring connection, for France and other countries, with extended accidental contact protection/safety device, green, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, NFC61-314

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0804021

Packing unit 1

Catalog page Page 565 (C-3-2019)

GTIN 4055626225630

Custom tariff number 85366990

Drawings

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

General

Standards and Regulations

Classifications

Drawings

Circuit diagram

[Back to top](#)Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display No

Contact material CuZn37

Color green

6021

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations NF C61-314

Country ID France

[Back to top](#)Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Push-in spring connection

[Back to top](#)Standards and Regulations

Standards/regulations NF C61-314

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7.0 27142305

eCl@ss 8.0 27142305

eCl@ss 9.0 27142305

[Back to top](#)ETIM

ETIM 5.0....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-E/PT/SH/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.