

INDUSTRIAL COMPONENT DATA

EO-E/UT/SH/LED/YE 1068076 PHOENIX CONTACT Socket, Pin connector pattern type E, for France and other countries..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-E/UT/SH/LED/YE



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-E/UT/SH/LED/YE
Catalog number	1068076
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-971EF5DA7A
Generated	2026-08-01

Product Overview

Socket, Pin connector pattern type E, for France and other countries, with extended touch proofness/shutter, LED display, yellow, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, NF C61-314 Power socket, Type E plug-in face, for France and other countries, with extended accidental contact protection/safety device, light indication, yellow, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, NFC61-314

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 1068076

Packing unit 1 pc

Minimum order quantity 5 pc

Catalog page Page 565 (C-3-2019)

GTIN 4055626738987

Weight per Piece (excluding packing) 72.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Drawings

Ambient conditions

[Connection data](#)

[Classifications](#)

[Dimensions](#)

[General](#)

[Standards and Regulations](#)

[Drawings](#)

[Circuit diagram](#)

[Back to top](#)[Dimensions](#)

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to top](#)[Ambient conditions](#)

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)[General](#)

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display Yes

Contact material CuZn37

Color yellow

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations NF C61-314

Country ID France

[Back to top](#)[Connection data](#)

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

[Back to top](#)[Standards and Regulations](#)

Standards/regulations NF C61-314

Flammability rating according to UL 94 V0

[Back to top](#)[Classifications](#)

eCI@ss

eCI@ss 8.0 27142305

eCI@ss 9.0 27142305

[Back to top](#)[ETIM](#)

ETIM 5.0 EC001663

ETIM 6.0 EC001663

ETIM 7.0 EC001663

[Back to top](#)

ETIM for 1068076 Modular devices for distribution board/surface mounting (EC001663)

Feature Name

Feature Value

Rated voltage (EF000228)

250 V

Rated current (EF000227)

16 A

With hinged lid (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-E/UT/SH/LED/YE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.