

INDUSTRIAL COMPONENT DATA

EO-G/PT/SH/LED/GN 0804066 PHOENIX CONTACT Socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-G/PT/SH/LED/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-G/PT/SH/LED/GN
Catalog number	0804066
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-C46B4555D8
Generated	2026-07-28

Product Overview

Socket

Power socket, Type G plug-in face, Push-in spring connection, for Great Britain and other countries, with extended accidental contact protection/safety device, light indication, green, for rail mounting at the service interface or direct mounting, 250 VAC, 13 A, -20 °C, 60 °C, BS1363-1/-2

Socket, Pin connector pattern type G, for Great Britain and other countries, with extended touch proofness/shutter, LED display, green, for mounting on a DIN rail in the service interface or direct mounting, -5 °C, 40 °C, BS 1363-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Technical dataProduct propertiesProduct type Socket

Country ID Great Britain

Data management status

Article revision 04

Connection dataStripping length 10 mm

Internal cylindrical gage A3

B3

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.25 mm² ... 2.5 mm²

Conductor cross section, flexible [AWG] 24 ... 14 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 2.5 mm²
Conductor cross-section flexible (2 conductors with the same cross-section, with TWIN ferrule and plastic sleeve) 0.25 mm² ... 2.5 mm²
Nominal current 13 A
Nominal voltage 250 V AC (50 Hz)
Connection cross sections directly pluggable
Conductor cross section rigid 0.5 mm² ... 4 mm²
Conductor cross-section flexible (ferrule without plastic sleeve) 1 mm² ... 2.5 mm²
Flexible conductor cross section (ferrule with plastic sleeve) 1 mm² ... 2.5 mm²
SignalingStatus display yes
DimensionsWidth 45 mm
Height 75 mm
Depth 75 mm
Material specificationsColor green (RAL 6021)
Flammability rating according to UL 94 V0
Insulating material PA
Contact material CuZn37
Static insulating material application in cold -60 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-G/PT/SH/LED/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.