

INDUSTRIAL COMPONENT DATA**EO-G/UT/SH/S 0804058 PHOENIX CONTACT Socket**

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-G/UT/SH/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-G/UT/SH/S
Catalog number	0804058
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-804A70C41D
Generated	2026-08-01

Product Overview

Socket

Power socket, Type G plug-in side, Screw connection, for Great Britain and other countries, with extended accidental contact protection/safety device, switch, grey, for rail mounting at service interface or direct mounting, 250 VAC, 13 A, -20 °C, 60 °C, BS1363-1/-2

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **PHOENIX CONTACT > CABINET add-on****Additional Product Information**

Key Commercial Data

Orderkey 0804058

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 609 (C-3-2017)

GTIN 4055626225968

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 13 A

Status display No

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations BS 1363-1/-2

Country ID Great Britain

Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

Standards and Regulations

Standards/regulations BS 1363-1/-2

Flammability rating according to UL 94 V0

Environmental Product Compliance

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Classifications

eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss 7.027142305eCl@ss 8.027142305eCl@ss 9.027142305

ETIM 5.0EC001663ETIM 6.0EC001663

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-G/UT/SH/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.