

INDUSTRIAL COMPONENT DATA

EO-I/UT 0804087 PHOENIX CONTACT Socket, Pin connector pattern type I, Screw connection, for China/Australia ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-I/UT



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-I/UT
Catalog number	0804087
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-4F004EE528
Generated	2026-08-04

Product Overview

Socket, Pin connector pattern type I, Screw connection, for China/Australia and other countries, gray, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 10 A, -20 °C, 60 °C, GB 2099.1 and GB 1002

Power Outlet, Type I Plug-in Face, Screw Connection, for China/Australia and Other Countries, Grey, for Rail Mounting at Service Interface or Direct Mounting, 250 VAC, 10 A, -20°C, 60 °C, GB209.1 and GB1002

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804087

Packing unit 1 pc

Minimum order quantity 5 pc

Catalog page Page 567 (C-3-2019)

GTIN 4055626226224

Weight per Piece (excluding packing) 76.000 g

Custom tariff number 85366990

Country of origin PL (Poland)

Dimensions

General

Standards and Regulations

Classifications

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 10 A

Status display No

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations GB 2099.1 and GB 1002

Country ID China

[Back to top](#)Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

[Back to top](#)Standards and Regulations

Standards/regulations GB 2099.1 and GB 1002

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-I/UT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.