

## INDUSTRIAL COMPONENT DATA

# EO-I/UT/GN 0804088 PHOENIX CONTACT Prise, Modèle d'enfichage de type I, Raccordement vissé, pour la Chine / ..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-I/UT/GN



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | PHOENIX CONTACT                      |
| MPN / Reference | EO-I/UT/GN                           |
| Catalog number  | 0804088                              |
| Category        | Socket outlet for distribution board |
| Minimum order   | 5 Pcs                                |
| Document ID     | EO-2590041053                        |
| Generated       | 2026-08-06                           |

## Product Overview

Prise, Modèle d'enfichage de type I, Raccordement vissé, pour la Chine / Australie et autres pays, vert, pour montage sur profilé dans une interface de service ou pour montage direct, 250 V AC, 10 A, -20 °C, 60 °C, GB 2009.1 et GB 1002  
Power Outlet, Type I Plug-in Face, Screw Connection, for China/Australia and Other Countries, Green, for Rail Mounting at Service Interface or Direct Mounting, 250 VAC, 10 A, -20 °C, 60 °C, GB2009.1 and GB1002

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; CABINET add-on

## Additional Product Information

Key Commercial Data

Orderkey 0804088

Packing unit 1

Catalog page Page 567 (C-3-2019)

GTIN 4055626226231

Custom tariff number 85366990

Dimensions

General

Standards and Regulations

Classifications

Ambient conditions

Connection data

[Environmental Product Compliance](#)

[Dimensions](#)

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to topAmbient conditions](#)

Ambient temperature (operation) -20 °C ... 60 °C

[Back to topGeneral](#)

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 10 A

Status display No

Contact material CuZn37

Color green

6021

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations GB 2099.1 and GB 1002

Country ID China

[Back to topConnection data](#)

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 4 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

[Back to topStandards and Regulations](#)

Standards/regulations GB 2099.1 and GB 1002

Flammability rating according to UL 94 V0

[Back to topEnvironmental Product Compliance](#)

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

[Back to topClassifications](#)

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7.0 27142305

eCl@ss 8.0 27142305

eCl@ss 9.0 27142305

[Back to topETIM](#)

ETIM 5.0 EC00166...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-I/UT/GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.