

INDUSTRIAL COMPONENT DATA

EO-I/UT/LED/DUO/GN 0804092 PHOENIX CONTACT Double socket, Pin connector pattern type I, Screw connection, fo..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-I/UT/LED/DUO/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-I/UT/LED/DUO/GN
Catalog number	0804092
Category	Socket outlet for distribution board
Minimum order	2 Pcs
Document ID	EO-3025216E6D
Generated	2026-08-03

Product Overview

Double socket, Pin connector pattern type I, Screw connection, for China/Australia and other countries, LED display, green, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 10 A, -20 °C, 60 °C, GB 2099.1 and GB 1002

Dual Power Outlet, Type I Plug-in Side, Screw Connection, for China/Australia and Other Countries, Indicator Light, Green, for Rail Mounting at Service Interface or Direct Mounting, 250 VAC, 10 A, -20 °C, 60 °C, GB2099.1 and GB1002

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804092

Packing unit 1

Catalog page Page 567 (C-3-2019)

GTIN 4055626226279

Custom tariff number 85366990

Drawings

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

General

Standards and Regulations

Classifications

Drawings

Circuit diagram

Back to topDimensions

Width 90 mm

Height 75 mm

Depth 57.5 mm

Back to topAmbient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Back to topGeneral

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 10 A

Status display Yes

Contact material CuZn37

Color green

6021

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations GB 2099.1 and GB 1002

Country ID China

Back to topConnection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

Back to topStandards and Regulations

Standards/regulations GB 2099.1 and GB 1002

Flammability rating according to UL 94 V0

Back to topEnvironmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Back to topClassifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-I/UT/LED/DUO/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.