

INDUSTRIAL COMPONENT DATA

EO-J/PT/LED/DUO/GN 0804111 PHOENIX CONTACT Double socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-J/PT/LED/DUO/GN



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-J/PT/LED/DUO/GN
Catalog number	0804111
Category	Socket outlet for distribution board
Minimum order	2 Pcs
Document ID	EO-38DFAA0E38
Generated	2026-08-01

Product Overview

Double socket

Dual power outlet, Plug-in side type J, Push-in spring connection, with indicator light, for Switzerland and other countries, green, for rail mounting at the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, SEV 1011

Double socket, Pin connector pattern type J, Push-in spring connection, with LED display, for Switzerland and other countries, green, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, SEV 1011

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Technical dataProduct propertiesProduct type Socket

Country ID Switzerland

Electrical propertiesNominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Connection dataConnection method Push-in spring connection

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)

SignalingStatus display Yes

DimensionsWidth 90 mm

Height 75 mm
Depth 75 mm
Material specificationsColor green
Flammability rating according to UL 94 V0
Insulating material PA
Contact material CuZn37
Static insulating material application in cold -60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C
Relative insulation material temperature index (Elec., UL 746 B) 130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24 HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26 HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162) passed
Specific optical density of smoke NFPA 130 (ASTM E 662) passed
Smoke gas toxicity NFPA 130 (SMP 800C) passed
ConnectorType of plug Pin connector pattern type J
Environmental and real-life conditionsAmbient conditions
Degree of protection IP20
Ambient temperature (operation) -20 °C ... 60 °C (max. short-term operating temperature RTI Elec.)
Ambient t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-J/PT/LED/DUO/GN with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.