

## INDUSTRIAL COMPONENT DATA

## EO-K/UT/LED/GN 0804116 PHOENIX CONTACT Socket

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-K/UT/LED/GN



|                 |                                      |
|-----------------|--------------------------------------|
| Manufacturer    | PHOENIX CONTACT                      |
| MPN / Reference | EO-K/UT/LED/GN                       |
| Catalog number  | 0804116                              |
| Category        | Socket outlet for distribution board |
| Minimum order   | 5 Pcs                                |
| Document ID     | EO-0204F79B7C                        |
| Generated       | 2026-08-01                           |

## Product Overview

## Socket

Power socket, Type K plug-in face, Screw connection, for Denmark and other countries, with indicator light, green, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, SR107-2-D1

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

|              |                                  |
|--------------|----------------------------------|
| Catalog path | PHOENIX CONTACT > CABINET add-on |
|--------------|----------------------------------|

## Additional Product Information

## Key Commercial Data

Orderkey 0804116

Packing unit 5 pc

Minimum order quantity 5 pc

Note Made to Order (non-returnable)

Catalog page Page 611 (C-3-2017)

GTIN 4055626226491

Weight per Piece (excluding packing) 9.990 g

Custom tariff number 85366990

Country of origin PL (Poland)

## Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

**Ambient conditions**

Ambient temperature (operation) -20 °C ... 60 °C

**General**

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display Yes

Contact material CuZn37

Color green

6021

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations SR 107-2-D1

Country ID Denmark

**Connection data**

Conductor cross section solid min. 0.2 mm<sup>2</sup>

Conductor cross section solid max. 4 mm<sup>2</sup>

Conductor cross section flexible min. 0.2 mm<sup>2</sup>

Conductor cross section flexible max. 2.5 mm<sup>2</sup>

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

**Standards and Regulations**

Standards/regulations SR 107-2-D1

Flammability rating according to UL 94 V0

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

**Classifications**

eCl@ss 5.127142300eCl@ss 6.027142300eCl@ss 7.027142305eCl@ss 8.027142305eCl@ss 9.027142305

ETIM 5.0EC001663ETIM 6.0EC001663

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send PHOENIX CONTACT / EO-K/UT/LED/GN with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.