

INDUSTRIAL COMPONENT DATA

EO-L/UT/SH 0804126 PHOENIX CONTACT Socket, Pin connector pattern type L, Screw connection, for Italy and oth..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-L/UT/SH



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-L/UT/SH
Catalog number	0804126
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-6EF9533166
Generated	2026-08-03

Product Overview

Socket, Pin connector pattern type L, Screw connection, for Italy and other countries, with extended touch proofness/shutter, gray, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, CEI 23-50

Power socket, Plug-in face type L, Screw connection, for Italy and other countries, with extended contact protection/safety device, grey, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, CEI23-50

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804126

Packing unit 1

Catalog page Page 564 (C-3-2019)

GTIN 4055626226583

Custom tariff number 85366990

Dimensions

General

Standards and Regulations

Classifications

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

Back to topAmbient conditions

Ambient temperature (operation) -20 °C ... 60 °C

Back to topGeneral

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display No

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations CEI 23-50

Country ID Italy

Back to topConnection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

Back to topStandards and Regulations

Standards/regulations CEI 23-50

Flammability rating according to UL 94 V0

Back to topEnvironmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally friendly use period: unlimited = EFUP-e

No hazardous substances above threshold values

Back to topClassifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7.0 27142305

eCl@ss 8.0 27142305

eCl@ss 9.0 27142305

Back to topETIM

ETIM 5.0 EC001663

ETIM 6.0 EC001663

ETIM....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-L/UT/SH with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.