

INDUSTRIAL COMPONENT DATA

EO-L/UT/SH/LED 0804128 PHOENIX CONTACT Socket, Pin connector pattern type L, Screw connection, for Italy and..

Brand: PHOENIX CONTACT | Manufacturer Part Number: EO-L/UT/SH/LED



Manufacturer	PHOENIX CONTACT
MPN / Reference	EO-L/UT/SH/LED
Catalog number	0804128
Category	Socket outlet for distribution board
Minimum order	5 Pcs
Document ID	EO-2D0BB67464
Generated	2026-08-01

Product Overview

Socket, Pin connector pattern type L, Screw connection, for Italy and other countries, with extended touch proofness/shutter, LED display, gray, for mounting on a DIN rail in the service interface or direct mounting, 250 V AC, 16 A, -20 °C, 60 °C, CEI 23-50

Power socket, Plug-in face type L, Screw connection, for Italy and other countries, with extended accidental contact protection/safety device, indicator light, grey, for rail mounting at the service interface or direct mounting, 250 VAC, 16 A, -20 °C, 60 °C, CEI23-50

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > CABINET add-on

Additional Product Information

Key Commercial Data

Orderkey 0804128

Packing unit 1

Catalog page Page 564 (C-3-2019)

GTIN 4055626226606

Custom tariff number 85366990

Drawings

Ambient conditions

Connection data

Environmental Product Compliance

Dimensions

General

Standards and Regulations

Classifications

Drawings

Circuit diagram

[Back to top](#)Dimensions

Width 45 mm

Height 75 mm

Depth 57.5 mm

[Back to top](#)Ambient conditions

Ambient temperature (operation) -20 °C ... 60 °C

[Back to top](#)General

Nominal voltage UN 250 V AC (50 Hz)

Nominal current IN 16 A

Status display Yes

Contact material CuZn37

Color gray

7042

Insulating material PA

Flammability rating according to UL 94 V0

Standards/regulations CEI 23-50

Country ID Italy

[Back to top](#)Connection data

Conductor cross section solid min. 0.2 mm²

Conductor cross section solid max. 4 mm²

Conductor cross section flexible min. 0.2 mm²

Conductor cross section flexible max. 2.5 mm²

Conductor cross section AWG min. 24

Conductor cross section AWG max. 12

Connection method Screw connection

[Back to top](#)Standards and Regulations

Standards/regulations CEI 23-50

Flammability rating according to UL 94 V0

[Back to top](#)Environmental Product Compliance

REACH SVHC

Lead 7439-92-1

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

[Back to top](#)Classifications

eCl@ss

eCl@ss 4.0 27142300

eCl@ss 4.1 27142300

eCl@ss 5.0 27142300

eCl@ss 5.1 27142300

eCl@ss 6.0 27142300

eCl@ss 7.0 27142305

eCl@ss 8.0 27...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / EO-L/UT/SH/LED with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.