

INDUSTRIAL COMPONENT DATA

ESSENTIAL-PS/1AC/24DC/240W/EE 2910587 PHOENIX
CONTACT ?????????? ????????

Brand: PHOENIX CONTACT | Manufacturer Part Number: ESSENTIAL-PS/1AC/24DC/240W/EE



Manufacturer	PHOENIX CONTACT
MPN / Reference	ESSENTIAL-PS/1AC/24DC/240W/EE
Catalog number	2910587
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-B5018E4BBF
Generated	2026-08-04

Product Overview

?????????? ????????

ESSENTIAL edition primary switching power supply for rail mounting, input: single-phase, output: 24 V DC/240 W

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Power Supplies (PS)

Additional Product Information

Key Commercial Data

Orderkey 2910587

Packing unit 1 pc

GTIN 4055626464404

Weight per Piece (excluding packing) 966.600 g

Custom tariff number 85044030

Country of origin TH (Thailand)

Dimensions

Width 60 mm

Height 123.6 mm

Depth 117.6 mm

Installation distances left/right 10 mm

Installation distances top/bottom 50 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -20 °C ... 70 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Max. permissible relative humidity (operation) ≤ 95 % (at 25 °C, non-condensing)

Degree of pollution 2

Installation height ≤ 5000 m (> 2000 m, Derating: 10 %/1000 m)

Input data

Nominal input voltage range 100 V AC ... 240 V AC

Input voltage range 85 V AC ... 264 V AC

AC frequency range 47 Hz ... 63 Hz

Discharge current to PE < 1 mA (264 V AC)

Current consumption 2.8 A (115 V AC)

1.4 A (230 V AC)

Inrush surge current typ. 20 A (115 V AC)

typ. 40 A (230 V AC)

Mains buffering typ. 10 ms (115 V AC)

typ. 16 ms (230 V AC)

Input fuse 6.3 A (slow-blow, internal)

Type of protection Transient surge protection

Protective circuit/component Varistor

Output data

Nominal output voltage 24 V DC ±2 %

Setting range of the output voltage (USet) 22 V DC ... 28 V DC (max. power ≤ 240 W)

Nominal output current (IN) 10 A

Derating > 40 °C (1.67 % / °C, 115 V AC)

> 50 °C (2.5 % / °C, 230 V AC)

Max. capacitive load 8000 µF

Active current limitation 105% - 150% of the max. output power (in the event of short circuit)

Residual ripple < 120 mVP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / ESSENTIAL-PS/1AC/24DC/240W/EE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.