

INDUSTRIAL COMPONENT DATA

VS-IP67/B-IP20-94F-LI/5,0 1415526 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-IP67/B-IP20-94F-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-IP67/B-IP20-94F-LI/5,0
Catalog number	1415526
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-45F82519E5
Generated	2026-08-03

Product Overview

Network cable

Ready-made Ethernet cable, CAT6, shielded, 4 pairs, flexible AWG 26 (7 wires), RAL 5021 (aqua blue), RJ45/IP67 male connector, black, to RJ45/IP20 male connector, Line, length 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Field Device Connectors (FDC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1415526

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 209 (PC-2009)

GTIN 4046356474924

Weight per Piece (excluding packing) 231.700 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP20

IP67

Ambient temperature (operation) -25 °C ... 60 °C (cable, fixed installation)

-10 °C ... 50 °C (cable, flexible installation)

General data

Number of positions 8

Degree of pollution 2

Alternative short product description Ethernet cable

Characteristics head 1

Color black

Characteristics head 2

Color gray

Standards and Regulations

Flammability rating according to UL 94 V2

Cable

Cable type Ethernet 10 Gbit

Cable type (abbreviation) 94F

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT6A, 10 Gbps

Cable structure 4x2xAWG26/7; S/FTP

Conductor cross section 4x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 1.04 mm

Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown

Twisted pairs 2 cores to the pair

Type of pair shielding Aluminum-lined foil

Overall twist 4 pairs for core

Shielding Tinned copper braided shield

Optical shield covering 70 %

External sheath, color water blue RAL 5021

Outer sheath thickness 0.65 mm

External cable diameter D 6.4 mm ±0.2 mm

Minimum bending radius, fixed installation 4 x D

Minimum bending radius, flexible installation 8 x D

Tensile strength GRP ≤ 100 N

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-IP67/B-IP20-94F-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.