

INDUSTRIAL COMPONENT DATA

VS-IP67-IP20-94F-LI/5,0 1415490 PHOENIX CONTACT Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-IP67-IP20-94F-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-IP67-IP20-94F-LI/5,0
Catalog number	1415490
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A48311C5A3
Generated	2026-08-04

Product Overview

Network cable

Ready-made Ethernet cable, CAT6, shielded, 4 pairs, flexible AWG 26 (7 wires), RAL 5021 (aqua blue), RJ45/IP67 male connector, grey, to RJ45/IP20 male connector, Line, length 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1415490

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 208 (PC-2009)

GTIN 4046356474917

Weight per Piece (excluding packing) 254.600 g

Custom tariff number 85444210

Country of origin PL (Poland)

Ambient conditions

Degree of protection IP20

IP67

Ambient temperature (operation) -25 °C ... 60 °C (cable, fixed installation)

-10 °C ... 50 °C (cable, flexible installation)

General data

Number of positions 8

Degree of pollution 2

Alternative short product description Ethernet cable

Standards and Regulations

Flammability rating according to UL 94 V2

Cable

Cable type Ethernet 10 Gbit

Cable type (abbreviation) 94F

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT6A, 10 Gbps

Cable structure 4x2xAWG26/7; S/FTP

Conductor cross section 4x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 1.04 mm

Wire colors white/blue-blue, white/orange-orange, white/green-green, white/brown-brown

Twisted pairs 2 cores to the pair

Type of pair shielding Aluminum-lined foil

Overall twist 4 pairs for core

Shielding Tinned copper braided shield

Optical shield covering 70 %

External sheath, color water blue RAL 5021

Outer sheath thickness 0.65 mm

External cable diameter D 6.4 mm ±0.2 mm

Minimum bending radius, fixed installation 4 x D

Minimum bending radius, flexible installation 8 x D

Tensile strength GRP ≤ 100 N

Cable weight 42 kg/km

Outer sheath, material PUR

Material conductor in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-IP67-IP20-94F-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.