

INDUSTRIAL COMPONENT DATA

VS-M8MS-M8MS/93B-0,5 1402448 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-M8MS-M8MS/93B-0,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-M8MS-M8MS/93B-0,5
Catalog number	1402448
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-3E0463515B
Generated	2026-08-02

Product Overview

Network cable

Network cable, Ethernet (100 MBit/s), PROFINET (100 MBit/s), EtherCAT® (100 MBit/s), 4-pole, M8 straight connector, encoding: A/IP67, a M8 straight connector, encoding: A/IP67, cable length: 0.5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Industrial Field Connectivity (IFC)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1402448

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 322 (PC-2011)

GTIN 4046356616058

Weight per Piece (excluding packing) 57.500 g

Custom tariff number 85444290

Country of origin PL (Poland)

Dimensions

Length of cable 0.5 m

Ambient conditions

Degree of protection IP65

IP67

General data

Rated current at 40°C 3 A

Rated voltage 30 V AC

30 V DC

Number of positions 4

Signal type/category Ethernet, 100 Mbps

PROFINET, 100 Mbps

EtherCAT®, 100 Mbps

Standards/regulations M8 connector IEC 61076-2-104

Overvoltage category II

Degree of pollution 3

Characteristics head 1

Head type Plug straight M8 / IP67

No. of positions (pin connector pattern) 4 (4)

Color black

Material (component) CuSn (Contact)

Ni/Au (Contact surface)

TPU GF (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip)

CuZn (nickel-plated) (Screw connection)

Shielded yes

Insulation resistance $\geq 100 \text{ M}\Omega$ Insertion/withdrawal cycles ≥ 100

Torque 0.2 Nm

Ambient temperature (operation) -25 °C ... 90 °C

Characteristics head 2

Head type Plug straight M8 / IP67

No. of positions (pin connector pattern) 4 (4)

Color black

black

Material (component) CuSn (Contact)

Ni/Au (Contact surface)

CuZn (nickel-plated) (Screw connection)

TPU GF (Contact carriers)

TPU, hardly inflammable, self-extinguishing (Grip)

Shielded yes

Insulation resistance $\geq 100 \text{ M}\Omega$ Insertion/withdrawal cycles ≥ 100

Torque 0.2 Nm

Ambient temperature (operation) -25 °C ... 90 °C

Standards and Regulations

S...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-M8MS-M8MS/93B-0,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.