

INDUSTRIAL COMPONENT DATA

VS-PPC/ME-OE-93E-LI/5,0 1405743 PHOENIX CONTACT

Network cable

Brand: PHOENIX CONTACT | Manufacturer Part Number: VS-PPC/ME-OE-93E-LI/5,0



Manufacturer	PHOENIX CONTACT
MPN / Reference	VS-PPC/ME-OE-93E-LI/5,0
Catalog number	1405743
Category	Sensor-actuator patch cord
Minimum order	1 Pcs
Document ID	EO-A220B798F0
Generated	2026-08-03

Product Overview

Network cable

Ready-made Ethernet cable, CAT5e, shielded, 2 pairs, flexible AWG 26 (7 wires), RAL 5021 (aqua blue), RJ45/IP67 male connector, push-pull, metal housing, to free cable end, Line, length 5 m

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Field Device Connectors (FDC)

Additional Product Information

Key Commercial Data

Orderkey 1405743

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 402 (C-2-2017)

GTIN 4046356475938

Weight per Piece (excluding packing) 305.200 g

Custom tariff number 85444210

Country of origin PL (Poland)

Dimensions

Length of cable 5.00 m

Ambient conditions

Degree of protection IP65

IP67

General data

Number of positions 4

Standards/regulations IEC PAS 61076-3-117

Degree of pollution 2

Alternative short product description Ethernet cable

Locking type Push Pull

Standards and Regulations

Standards/regulations IEC PAS 61076-3-117

Flammability rating according to UL 94 V2

Cable

Cable type PUR ETHERNET 2x2 FLEX

Cable type (abbreviation) 93E

UL AWM style 20963 (80°C/30 V)

Signal type/category Ethernet CAT5 (IEC 11801), 100 Mbps

Cable structure 2x2xAWG26/7; SF/UTP

Conductor cross section 2x 2x 0.14 mm²

AWG signal line 26

Conductor structure signal line 7x 0.16 mm

Core diameter including insulation 0.98 mm

Wire colors white/orange-orange, white/green-green

Twisted pairs 2 cores to the pair

Overall twist Two pairs with two fillers to the core

Shielding Aluminum-coated foil, tinned copper braided shield

Optical shield covering 70 %

External sheath, color water blue RAL 5021

Outer sheath thickness 1.2 mm

External cable diameter D 6.4 mm ±0.2 mm

Minimum bending radius, fixed installation 4 x D

Minimum bending radius, flexible installation 8 x D

Tensile strength GRP ≤ 80 N

Cable weight 42 kg/km

Outer sheath, material PUR

Material conductor insu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / VS-PPC/ME-OE-93E-LI/5,0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.