

INDUSTRIAL COMPONENT DATA

FL SWITCH SFN 16TX 2891933 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH SFN 16TX



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH SFN 16TX
Catalog number	2891933
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-772304ABB8
Generated	2026-07-29

Product Overview

Industrial Ethernet Switch

Ethernet Switch, 16 TP-RJ45 ports, automatic data rate recording of 10 or 100 Mbps/s (RJ45), Autocrossing function

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2891933

Packing unit 1 pc

Catalog page Page 391 (C-6-2017)

GTIN 4046356551588

Weight per Piece (excluding packing) 871.000 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 70 mm

Height 135 mm

Depth 110 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) 0 °C ... 60 °C

Ambient temperature (storage/transport) -40 °C ... 85 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 86 kPa ... 108 kPa (up to 1500 m above sea level)

Air pressure (storage/transport) 66 kPa ... 108 kPa (up to 3500 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 16 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Transmission length 100 m (per segment)

Function

Basic functions Unmanaged switch / auto negotiation, complies with IEEE 802.3, store-and-forward switching mode, includes alarm contacts

Additional functions Autonegotiation

Status and diagnostic indicators LEDs: US1, US2(redundant voltage supply), link and activity per port

Signal contact control voltage 24 V DC

Signal contact control current 1 A

Network expansion parameters

Cascading depth Network, linear, and star structu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH SFN 16TX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.