

INDUSTRIAL COMPONENT DATA

FL SWITCH SFN 8TX 2891929 PHOENIX CONTACT Industrial Ethernet Switch

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL SWITCH SFN 8TX



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL SWITCH SFN 8TX
Catalog number	2891929
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-4C127B0B1E
Generated	2026-07-31

Product Overview

Industrial Ethernet Switch

Ethernet switch, 8 TP-RJ45 ports, 10/100 Mbps/s (RJ45) automatic data rate detection, autocrossing function

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > I/O
--------------	-----------------------

Additional Product Information

Key Commercial Data

Orderkey 2891929

Packing unit 1 pc

Catalog page Page 389 (C-6-2017)

GTIN 4046356100823

Weight per Piece (excluding packing) 494.200 g

Custom tariff number 85176200

Country of origin TW (Taiwan)

Dimensions

Width 50 mm

Height 120 mm

Depth 70 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) 0 °C ... 60 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Permissible humidity (operation) 5 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 5 % ... 95 % (non-condensing)

Air pressure (operation) 86 kPa ... 108 kPa (up to 1500 m above sea level)

Air pressure (storage/transport) 66 kPa ... 108 kPa (up to 3500 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 8 (RJ45 ports)

Note on the connection method Auto negotiation and autocrossing

Transmission physics Ethernet in RJ45 twisted pair

Transmission speed 10/100 Mbps

Function

Basic functions Unmanaged switch / auto negotiation, complies with IEEE 802.3, store and forward switching mode

Additional functions Autonegotiation

Status and diagnostic indicators LEDs: US, link and activity per port

Network expansion parameters

Cascading depth Network, linear, and star structure: any

Maximum conductor length (twisted pair) 100 m

Supply voltage

Supply voltage 24 V DC

Residual ripple 3.6 VPP(within the permitted voltage range)

Supply voltage range 9 V DC ... 32 V DC

Typical current consumption 140 mA (at US= 24 V DC)

General

Mounting type DIN rail

T...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL SWITCH SFN 8TX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.