

INDUSTRIAL COMPONENT DATA

F-MS 12-UD ST 2858328 PHOENIX CONTACT Type 2 surge protection plug

Brand: PHOENIX CONTACT | Manufacturer Part Number: F-MS 12-UD ST



Manufacturer	PHOENIX CONTACT
MPN / Reference	F-MS 12-UD ST
Catalog number	2858328
Category	Accessories/spare parts for surge protection power supply systems
Minimum order	1 Pcs
Document ID	EO-0C9FB66F8F
Generated	2026-08-05

Product Overview

Type 2 surge protection plug

Plug-in protection against type 2 surges, with N-PE sum current arc arrester, for base element.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Trabtech (TT)

Additional Product Information

Key Commercial Data

Orderkey 2858328

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 63 (C-4-2017)

GTIN 4017918878078

Weight per Piece (excluding packing) 35.380 g

Custom tariff number 85363010

Country of origin DE (Germany)

Dimensions

Height 52.4 mm

Width 17.5 mm

Depth 55.3 mm

Horizontal pitch 1 Div.

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) -40 °C ... 80 °C

Ambient temperature (storage/transport) -40 °C ... 80 °C

Altitude ≤ 2000 m (amsl (above mean sea level))

Permissible humidity (operation) 5 % ... 95 %

Shock (operation) 25g (Half-sine / 11 ms / 3x ±X, ±Y, ±Z)

Vibration (operation) 5g (10 ... 500 Hz / 2.5 h / X, Y, Z)

General

IEC test classification II

T2

EN type T2

Mode of protection N-PE

Mounting type on base element

Color jet black RAL 9005

Housing material PA 6.6

Degree of pollution 2

Flammability rating according to UL 94 V-0

Type DIN rail module, two-section, divisible

Arrester can be tested with CHECKMASTER from software version: From SW rev. 1.10

Surge protection fault message optical

Protective circuit

Nominal voltage UN 240/415 V AC (TN - only N-PE)

240/415 V AC (TT - only N-PE)

Nominal frequency fN 50 Hz (60 Hz)

Maximum continuous voltage UC 260 V AC

Residual current IPE ≤ 5 μA

Standby power consumption PC ≤ 1.5 mVA

Nominal discharge current In(8/20) μs 20 kA

Maximum discharge current I_{max}(8/20) μs 40 kA

Follow current interrupt rating I_{fi} 100 A (260 V)

Voltage protection level Up ≤ 1.5 kV

Residual vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / F-MS 12-UD ST with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.