

INDUSTRIAL COMPONENT DATA

BMK 20X 8 WH CUS 0824231 PHOENIX CONTACT Fabric label sheet

Brand: PHOENIX CONTACT | Manufacturer Part Number: BMK 20X 8 WH CUS



Manufacturer	PHOENIX CONTACT
MPN / Reference	BMK 20X 8 WH CUS
Catalog number	0824231
Category	Labelling for terminal block
Minimum order	1 Pcs
Document ID	EO-A4540A8FDC
Generated	2026-08-03

Product Overview

Fabric label sheet

Fabric label sheet, available: Elbow, white, labeled according to customer's instructions, mounting class: glued, usable surface: 20 mm x 8 mm, Number of individual indices: 270

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > CABINET add-on
--------------	----------------------------------

Additional Product Information

Key Commercial Data

Orderkey 0824231

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 293 (C-5-2013)

GTIN 4046356351096

Weight per Piece (excluding packing) 9.000 g

Custom tariff number 49119900

Country of origin DE (Germany)

Dimensions

Length (b) 8 mm

Width (a) 20 mm

Ambient conditions

Ambient temperature (operation) -40 °C ... 80 °C

General

Color white

Base element material Polyester foil

Components Silicone-free

Flammability rating according to UL 94 V0

Material Polyester foil

Number of individual labels 270

Adhesive Acrylic

Printability Plotter

Device 5144615 CMS-P1-PLOTTER

Test for substances that would hinder coating with paint or varnish VW PV 3.10.7:2005-02

Result Test passed

Test specification weathering-resistance Following ISO 4892-2:2013-03

Test duration 96 h

Wipe resistance test result Test passed

Salt spray test specification DIN EN 60068-2-11:2000-02

Test duration 96 h

Salt spray testing result Test passed

Alternating condensation climate with SO2 test specification DIN 50018:2013-05

Climate level AHT 1.0 S

Cycles 2

Condensation test result Test passed

Wipe resistance of test specification inscriptions DIN EN 61010-1 (VDE 0411-1):2011-07

Result Test passed

Marking mounting type adhesive

Standards and Regulations

Flammability rating according to UL 94 V0

Classifications

eCl@ss 10.0.127400629eCl@ss 4.024190219eCl@ss 4.124190219eCl@ss 5.027141137eCl@ss 5.127141100eCl@ss
6.027141100eCl@ss 7.027141137eCl@ss 8.027141137eCl@ss 9.027400629

ETIM....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / BMK 20X 8 WH CUS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.