

INDUSTRIAL COMPONENT DATA

FL PSE 2TX 2891013 PHOENIX CONTACT Ethernet module

Brand: PHOENIX CONTACT | Manufacturer Part Number: FL PSE 2TX



Manufacturer	PHOENIX CONTACT
MPN / Reference	FL PSE 2TX
Catalog number	2891013
Category	Network switch
Minimum order	1 Pcs
Document ID	EO-682EDE1E0E
Generated	2026-07-29

Product Overview

Ethernet module

Factoryline Power over Ethernet (PSE) module for Midspan power supply according to IEEE 802.3af, two PoE power ports, no configuration required, operation possible with 10 Mbits/s and 100 Mbits/s networks

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > I/O

Additional Product Information

Key Commercial Data

Orderkey 2891013

Packing unit 1 pc

Catalog page Page 401 (C-6-2017)

GTIN 4046356076043

Weight per Piece (excluding packing) 320.000 g

Custom tariff number 85176200

Country of origin DE (Germany)

Note

Utilization restriction EMC: class A product, see manufacturer's declaration in the download area

Dimensions

Width 45 mm

Height 99 mm

Depth 112 mm

Ambient conditions

Degree of protection IP20

Ambient temperature (operation) 0 °C ... 55 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

Permissible humidity (operation) 30 % ... 95 % (non-condensing)

Permissible humidity (storage/transport) 30 % ... 95 % (non-condensing)

Air pressure (operation) 86 kPa ... 108 kPa (2000 m above sea level)

Air pressure (storage/transport) 66 kPa ... 108 kPa (3500 m above sea level)

Interfaces

Interface 1 Ethernet (RJ45)

No. of ports 2 (RJ45 ports)

Transmission physics Copper

Transmission speed 10/100 Mbps

Transmission length 100 m (Between transmitter / receiver)

Signal LEDs PoE detection

Function

Basic functions PSE/midspan, complies with IEEE 802.3af

Status and diagnostic indicators LEDs: US, PoE detection per port

Network expansion parameters

Maximum conductor length (twisted pair) 100 m

Supply voltage

Supply voltage 24 V DC (via COMBICON; max. conductor cross section 2.5 mm²)

Residual ripple 3.6 VPP (within the permitted voltage range)

Supply voltage range 18.5 V DC ... 30.5 V DC

Typical current consumption typ. 100 mA (During no load; approx. 1800 mA at 24 V at the....)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FL PSE 2TX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.