


INDUSTRIAL COMPONENT DATA

FBS 50-3,5 3000706 PHOENIX CONTACT Plug-in bridge

Brand: PHOENIX CONTACT | Manufacturer Part Number: FBS 50-3,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	FBS 50-3,5
Catalog number	3000706
Category	Cross-connector for terminal block
Minimum order	10 Pcs
Document ID	EO-8F8528FDCA
Generated	2026-08-05

Product Overview

Plug-in bridge

Plug-in bridge, Variant with single or double-sided cutting edge. Please note the possible effects on protection against accidental contact, as well as the leakage lines and insulation distances in air., pitch: 3.5 mm, color: red

Plug-in bridge, pitch: 3.5 mm, number of positions: 50, color: red

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Technical dataNotesNote on application Version with single- or double-sided cutting edge. Please keep in mind the possible impact on touch protection

as well as air clearances and creepage distances.

Product propertiesProduct type Jumper

Number of positions 50

Pitch 3.5 mm

Data management status

Article revision 05

Electrical propertiesMaximum load current 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.)

Connection dataMaximum load current 17.5 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal

blocks.)

DimensionsPitch 3.5 mm

Material specificationsColor red (RAL 3001)

Material Copper

Flammability rating according to UL 94 V0

Insulating material PA

Environmental and real-life conditionsAmbient conditions

Ambient temperature (operation) -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)

Ambient temperature (storage/transport) -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)

Ambient temperature (assembly) -5 °C ... 70 °C

Ambient temperature (actuation) -5 °C ... 70 °C

Permissible humidity (operation) 20 % ... 90 %

Permissible humidity (storage/transport) 30 % ... 70 %

MountingMounting type Pl...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / FBS 50-3,5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.