

INDUSTRIAL COMPONENT DATA

DFLK-D62 SUBH/S 2300863 PHOENIX CONTACT Interface module

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFLK-D62 SUBH/S



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFLK-D62 SUBH/S
Catalog number	2300863
Category	Interface module
Minimum order	1 Pcs
Document ID	EO-F5CA63FB6C
Generated	2026-08-01

Product Overview

Interface module

VARIOFACE execution module, for direct coupling of individual signalling cables up to 2.5 mm², with subminiature plug strip D and screw connection, number of poles 62

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > INTERFACE Components (IF)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 2300863

Packing unit 10 pc

Note Made to Order (non-returnable)

Catalog page Page 311 (IF-2011)

GTIN 4017918903213

Weight per Piece (excluding packing) 189.230 g

Custom tariff number 85369010

Country of origin DE (Germany)

Dimensions

Width 40.4 mm

Height 180 mm

Ambient conditions

Ambient temperature (operation) -20 °C ... 50 °C

Ambient temperature (storage/transport) -20 °C ... 70 °C

General

Max. perm. operating voltage 25 V AC

50 V DC

Max. perm. current (per branch) 0.5 A

Number of positions 62

Status display No

Mounting position any

Assembly instructions In rows with zero spacing

Connection data for connection 1

Connection name Field level

Connection in acc. with standard IEC / EN

Connection method Screw connection

Stripping length 8 mm

Screw thread M3

Conductor cross section solid 0.2 mm² ... 4 mm²

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section AWG 24 ... 12

Connection data for connection 2

Connection name Controller level

Connection method D-SUB pin strip

Number of connections 1

Number of positions 62

Supported controller

Controller Teleperm XP

Standards and Regulations

Designation Air clearances and creepage distances

Standards/regulations DIN EN 50178

Rated surge voltage basic insulation

Degree of pollution 2

Overvoltage category II

Environmental Product Compliance

China RoHS Environmentally Friendly Use Period = 50

For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaratio..."

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFLK-D62 SUBH/S with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.