

INDUSTRIAL COMPONENT DATA

Q 0,75/4FL/11-M20KU-ESA BK 1641989 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: Q 0,75/4FL/11-M20KU-ESA BK



Manufacturer	PHOENIX CONTACT
MPN / Reference	Q 0,75/4FL/11-M20KU-ESA BK
Catalog number	1641989
Category	Sensor-actuator connector chassis
Minimum order	10 Pcs
Document ID	EO-9FC209697F
Generated	2026-08-05

Product Overview

Panel feed-through

QUICKON wall-mounted tooling, for external wall mounting with manual welding connection/flat plug connection, 2.8 mm x 0.8 mm. 4 poles.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > QUICKON Installation System (QPD)
--------------	---

Additional Product Information

Key Commercial Data

Orderkey 1641989

Packing unit 10 pc

Minimum order quantity 10 pc

Note Made to Order (non-returnable)

Catalog page Page 103 (PC-2011)

GTIN 4017918885250

Weight per Piece (excluding packing) 21.760 g

Custom tariff number 85369010

Country of origin PL (Poland)

General

Connection If the conductor is reconnected, it must be cut off above the last contact point. QUICKON components may only be operated when under no load.

Color black

Connection method QUICKON connection

Manual solder/slip-on connection; 2.8 x 0.8 mm

Number of positions 4

Wrench size, union nut 22 mm

Tightening torque, union nut 2.5 Nm

Wrench size, contact carrier 22 mm

Tightening torque contact carrier 3.75 Nm

Tightening torque, counter nut 3.75 Nm

Number of connections 4

Conductor cross section flexible min. 0.34 mm²

Conductor cross section flexible max. 0.75 mm²

Conductor cross section solid min. 0.75 mm²

Conductor cross section solid max. 1 mm²

Conductor cross section AWG min. 18

Conductor cross section AWG max. 16

Cable

Structure of individual litz in acc. with VDE 0295 / smallest wire diameter Class 2-6 // 0.34 mm²: 0.1 mm; 0.5 - 0.75 mm²: 0.15 mm

Wire insulation material PVC / PE

Wire diameter including insulation $\geq$ 2.5 mm

External cable diameter 6 mm ... 8 mm

Position marking 1, 2, 3, 4

Ambient conditions

Degree of protection IP65

IP67

Ambient temperature (operation) -25 °C ... 80 °C (Specifications of the cable manufacturer must be observed.)

-25 °C ... 50 °C (when the conductor is conn...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / Q 0,75/4FL/11-M20KU-ESA BK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.