

INDUSTRIAL COMPONENT DATA

QPD W 4PE2,5 6-11 M25 FC GY 1582571 PHOENIX CONTACT

Panel feed-through

Brand: PHOENIX CONTACT | Manufacturer Part Number: QPD W 4PE2,5 6-11 M25 FC GY



Manufacturer	PHOENIX CONTACT
MPN / Reference	QPD W 4PE2,5 6-11 M25 FC GY
Catalog number	1582571
Category	Sensor-actuator connector chassis
Minimum order	1 Pcs
Document ID	EO-CA398CC1A5
Generated	2026-08-06

Product Overview

Panel feed-through

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > QUICKON Installation System (QPD)

Additional Product Information

Key Commercial Data

Orderkey 1582571

Packing unit 1 pc

Note Made to Order (non-returnable)

Catalog page Page 170 (NTK-2012)

GTIN 4046356662031

Weight per Piece (excluding packing) 22.220 g

Custom tariff number 85366990

Country of origin PL (Poland)

General

Type QPD 5x2,5

Color gray

Locking type Screw locking

Connection method QUICKON connection

IDC connection

Number of positions 5
Note number of positions 4+PE
Wrench size, union nut 27 mm
Tightening torque, union nut 10 Nm
Tightening torque, counter nut 5 Nm
Wrench size, counter nut 30 mm
Number of connections 10
Conductor cross section flexible min. 1 mm²
Conductor cross section flexible max. 2.5 mm²
Conductor cross section solid min. 1 mm²
Conductor cross section solid max. 2.5 mm²
Conductor cross section AWG min. 16
Conductor cross section AWG max. 14
Dimensions of slip-on connection 4.8 x 0.8 mm
Cabel
Structure of individual litz in acc. with VDE 0295 / smallest wire diameter VDE 0295 class 1 to 6/min. 0.15 mm
Wire insulation material PVC/PE/TPE/rubber
Wire diameter including insulation 2 mm ... 3.8 mm
External cable diameter 6 mm ... 11 mm
Position marking 1, 2, L, N, PE
Ambient conditions
Degree of protection IP66
IP68 (2 m / 24 h)
IP69K
Ambient temperature (operation) -40 °C ... 100 °C
Ambient temperature (storage/transport) -40 °C ... 80 °C
Temperature when conductor connected -5 °C ... 50 °C
Electrical characteristics
Nominal current I_N 20 A
Rated current 20 A
Rated voltage (III/3) 690 V
Note on the rated voltage (I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / QPD W 4PE2,5 6-11 M25 FC GY with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.