

## INDUSTRIAL COMPONENT DATA

# UT 16 BK 3044197 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: UT 16 BK



|                 |                             |
|-----------------|-----------------------------|
| Manufacturer    | PHOENIX CONTACT             |
| MPN / Reference | UT 16 BK                    |
| Catalog number  | 3044197                     |
| Category        | Feed-through terminal block |
| Minimum order   | 50 Pcs                      |
| Document ID     | EO-36045A513D               |
| Generated       | 2026-08-01                  |

## Product Overview

Feed-through terminal block

Step terminal, rated voltage: 1000 V, rated current: 76 A, connection type: Screw connection, number of connections: 2, section: 1.5 mm<sup>2</sup> - 25 mm<sup>2</sup>, AWG: 16 - 4, width: 12.2 mm, height: 54.4 mm, colour: black, mounting class: NS 35/7.5, NS 35/15

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path PHOENIX CONTACT &gt; Modular TBs

## Additional Product Information

Key Commercial Data

Orderkey 3044197

Packing unit 50 pc

Minimum order quantity 50 pc

GTIN 4055626055275

Weight per Piece (excluding packing) 30.580 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 16 mm<sup>2</sup>  
Color black  
Insulating material PA  
Flammability rating according to UL 94 V0  
Area of application Railway industry  
Machine building  
Plant engineering  
Process industry  
Rated surge voltage 8 kV  
Degree of pollution 3  
Overvoltage category III  
Insulating material group I  
Maximum power dissipation for nominal condition 2.43 W  
Maximum load current 101 A (with 25 mm<sup>2</sup> conductor cross section)  
Nominal current I<sub>N</sub> 76 A  
Nominal voltage U<sub>N</sub> 1000 V  
Open side panel Yes  
Relative insulation material temperature index (Elec., UL 746 B) 130 °C  
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) 130 °C  
Static insulating material application in cold -60 °C  
Behavior in fire for rail vehicles (DIN 5510-2) Test passed  
Flame test method (DIN EN 60695-11-10) V0  
Oxygen index (DIN EN ISO 4589-2) >32 %  
NF F16-101, NF F10-102 Class I 2  
NF F16-101, NF F10-102 Class F 2  
Surface flammability NFPA 130 (ASTM E 162) passed  
Specific optical density of smoke NFPA 130 (ASTM E 662) passed  
Smoke gas toxicity NFPA 130 (SMP 800C) passed  
Calorimetric heat release NFPA 130 (ASTM E 1354) 28 MJ/kg  
Fire protection for rail vehicles (DIN EN 45545-2) R22 HL 1 - HL 3  
Fire protection for rail vehicles (DIN EN 45...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / UT 16 BK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.