


INDUSTRIAL COMPONENT DATA

DFK 4-PE 0708315 PHOENIX CONTACT PE panel panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: DFK 4-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	DFK 4-PE
Catalog number	0708315
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-7CABB9533A
Generated	2026-08-02

Product Overview

PE panel panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, number of poles: 1, charging current: 18 A, cross-section: 0.2 mm² - 6 mm², connection direction of the conductor with respect to the plug direction: 90 °, width: 6.1 mm, colour: green-yellow

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0708315

Packing unit 50 pc

Catalog page Page 639 (C-1-2013)

GTIN 4017918004590

Weight per Piece (excluding packing) 7.930 g

Custom tariff number 85369010

Country of origin BG (Bulgaria)

General

Number of levels 1

Number of connections 2

Nominal cross section 4 mm²

Color green-yellow
Insulating material PA
Flammability rating according to UL 94 V2
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-2
Nominal current I_N 17.5 A
Maximum load current 17.5 A
Nominal voltage U_N 400 V
Open side panel No
Number of positions 1
Dimensions
Width 6.2 mm
Length 29 mm
Pitch 6 mm
Plate thickness 1.5 mm
Connection data
Note Access
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 2.5 mm²
2 conductors with same cross section, solid min. 0.2 mm²
2 conductors with same cross section, solid max. 1.5 mm²
2 c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DFK 4-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.