


INDUSTRIAL COMPONENT DATA

DLKB 2,5-PE 3011038 PHOENIX CONTACT Motor terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: DLKB 2,5-PE



Manufacturer	PHOENIX CONTACT
MPN / Reference	DLKB 2,5-PE
Catalog number	3011038
Category	Ground terminal block
Minimum order	50 Pcs
Document ID	EO-70151B0A1F
Generated	2026-08-01

Product Overview

Motor terminal

Motor terminal block, four-storey, bridgeable, with PE foot, cross-section: 0.2 mm² - 4 mm², AWG: 24 - 12, connection type: screw connection, width: 6.2 mm, colour: grey, mounting type: NS 35/7.5, NS 35/15

Terminal block, nom. voltage: 400 V, nominal current: 19 A, connection method: Screw connection, Rated cross section: 2.5 mm², cross section: 0.2 mm² - 4 mm², mounting type: NS 35/7.5, NS 35/15, color: gray

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Motor terminal block

Number of connections 7

Number of rows 4

Potentials 4

Data management status

Article revision 08

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical propertiesRated surge voltage 6 kV

Maximum power dissipation for nominal condition 0.77 W

Connection dataGrounding foot Yes

Number of connections per level 2

Nominal cross section 2.5 mm²

Level 1+2+3

Screw thread M3

Note Please observe the current carrying capacity of the DIN rails.

Tightening torque 0.5 ... 0.6 Nm

Stripping length 8 mm

Internal cylindrical gage A3

Connection in acc. with standard IEC 60947-7-1/IEC 60947-7-2

Conductor cross section rigid 0.2 mm² ... 4 mm²

Cross section AWG 24 ... 12 (converted acc. to IEC)

Conductor cross section flexible 0.2 mm² ... 2.5 mm²

Conductor cross section, flexible [AWG] 24 ... 14 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.25 mm² ... 2.5 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.25 mm² ... 2.5 mm²

Cross-section with insertion bridge, rigid 4 mm²

Cross-section with insertion bridge, flexible 2.5 mm²

Nominal current 19 A

Maximum load current 24 A (with 4 mm² conductor cross section)

Nominal voltage 400 V (when using EB insertion bridges, the nominal voltage is reduced to 250 V.)

Nominal cross section 2.5 mm²

Dimensions Width 6.2 mm

Height 83.5 mm

Depth on NS 35/7,5 70 mm

Depth on NS 35/15 77.5 mm

Material specificati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / DLKB 2,5-PE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.