

INDUSTRIAL COMPONENT DATA

HDFK 10-VP-HV 0717393 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFK 10-VP-HV



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFK 10-VP-HV
Catalog number	0717393
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-0B6077B0A3
Generated	2026-08-01

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Weld connection, number of poles: 1, load current: 57 A, cross-section: 0.5 mm² - 16 mm², conductor connection direction with respect to the plug direction: 0 °, width: 10.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0717393

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 635 (CC-2009)

GTIN 4017918904623

Weight per Piece (excluding packing) 15.600 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2

Nominal cross section 10 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Rated surge voltage 6 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current I_N 57 A

Maximum load current 63 A

Nominal voltage U_N 1000 V

Number of positions 1

Dimensions

Width 10.1 mm

Length 58.8 mm

Pitch 10.1 mm

Connection data

Connection side outside

Connection method Screw connection

Conductor cross section solid min. 0.5 mm²

Conductor cross section solid max. 16 mm²

Conductor cross section flexible min. 0.5 mm²

Conductor cross section flexible max. 10 mm²

Conductor cross section AWG min. 20

Conductor cross section AWG max. 6

Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²

Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²

Conductor cross section flexible, with ferrule with plastic sleeve max. 10 mm²

2 conductors with same cross section, solid min. 0.5 mm²

2 conductors with same cross section, solid max. 4 mm²

2 conductors with same cross section, strand...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFK 10-VP-HV with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.