

INDUSTRIAL COMPONENT DATA

HDFK 25-VP/Z 0711205 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFK 25-VP/Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFK 25-VP/Z
Catalog number	0711205
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-6536B500D9
Generated	2026-08-02

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 101 A, cross-section: 6 mm² - 35 mm², conductor connection direction with respect to the plug direction: 0 °, width: 15 mm

Execution terminal, connection type: Screw connection with cage, Cable lug connection, number of poles: 1, load current: 101 A, cross-section: 6 mm² - 35 mm², conductor connection direction to insertion direction: 0 °, width: 15 mm, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 0711205

Packing unit 50 pc

Catalog page Page 635 (CC-2009)

GTIN 4017918311421

Weight per Piece (excluding packing) 48.640 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2
Nominal cross section 25 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 101 A
Maximum load current 125 A
Nominal voltage U_N 500 V
Open side panel No
Number of positions 1
Dimensions
Width 15.1 mm
Pitch 15.1 mm
Connection data
Note Terminal sleeve
Connection side outside
Connection method Screw connection
Conductor cross section solid min. 6 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 10 mm²
Conductor cross section flexible max. 25 mm²
Conductor cross section AWG min. 10
Conductor cross section AWG max. 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 25 mm²
2 conductors with same cross section, solid min. 2.5 mm²
2 conductors with same cross section, solid max. 10 mm²
2 conductors with same cross section, stranded min. 4...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFK 25-VP/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.