

**INDUSTRIAL COMPONENT DATA**

# HDFK 95-F-VP 0709916 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFK 95-F-VP



|                 |                                   |
|-----------------|-----------------------------------|
| Manufacturer    | PHOENIX CONTACT                   |
| MPN / Reference | HDFK 95-F-VP                      |
| Catalog number  | 0709916                           |
| Category        | Panel feed-through terminal block |
| Minimum order   | 10 Pcs                            |
| Document ID     | EO-16CC049D09                     |
| Generated       | 2026-08-01                        |

## Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Terminal connection, number of poles: 1, charging current: 232 A, cross-section: 35 mm<sup>2</sup> - 95 mm<sup>2</sup>, conductor connection direction with respect to the plug direction: 0 °, width: 25 mm

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      PHOENIX CONTACT &gt; PCB Connectors (PCC)

## Additional Product Information

Key Commercial Data

Orderkey 0709916

Packing unit 10 pc

Catalog page Page 619 (C-1-2013)

GTIN 4017918336660

Weight per Piece (excluding packing) 176.000 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2

Nominal cross section 95 mm<sup>2</sup>

Color gray

Insulating material PA

Flammability rating according to UL 94 V0

Maximum load current 232 A

Rated surge voltage 8 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Connection in acc. with standard IEC 60947-7-1

Nominal current IN 232 A

Maximum load current 232 A

Nominal voltage UN 630 V (metal panels 2.5 mm ... 5 mm)

500 V (metal panels 5 mm ... 6 mm)

Number of positions 1

Dimensions

Width 25 mm

Length 91.5 mm

Pitch 25 mm

Plate thickness 1 mm ... 6 mm

Connection data

Note Terminal sleeve

Connection side outside

Connection method Screw connection

Note Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area.

Conductor cross section solid min. 35 mm<sup>2</sup>

Conductor cross section solid max. 95 mm<sup>2</sup>

Conductor cross section flexible min. 35 mm<sup>2</sup>

Conductor cross section flexible max. 95 mm<sup>2</sup>

Conductor cross section AWG min. 4

Conductor cross section AWG max. 3/0

Conductor cross section flexible, with ferrule without plastic sleeve min. 30 mm<sup>2</sup>

Conductor cross section flexible, with ferrule without plastic sleeve max. 95 mm<sup>2</sup>

Conductor cross section flexible, with ferrule with plastic sleeve min. 3...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFK 95-F-VP with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.