

INDUSTRIAL COMPONENT DATA

HDFKV 10/Z 0714053 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFKV 10/Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFKV 10/Z
Catalog number	0714053
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-E9B82F6258
Generated	2026-08-01

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, load current: 57 A, cross-section: 0.5 mm² - 16 mm², conductor connection direction with respect to the plug direction: -90 °, width: 10.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0714053

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 629 (CC-2009)

GTIN 4046356180160

Weight per Piece (excluding packing) 21.550 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2
Nominal cross section 10 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 76 A
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current IN 57 A
Maximum load current 76 A
Nominal voltage UN 400 V (With metal panels of 1 mm ... 2.5 mm)
250 V (With metal panels over 2.5 mm ... 5 mm)
400 V (With plastic panels of 1 mm ... 4 mm)
Open side panel No
Number of positions 1
Dimensions
Width 10.1 mm
Length 49 mm
Pitch 10.1 mm
Connection data
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 0.5 mm²
Conductor cross section solid max. 16 mm²
Conductor cross section flexible min. 0.5 mm²
Conductor cross section flexible max. 10 mm²
Conductor cross section AWG min. 20
Conductor cross section AWG max. 6
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.5 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 10 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.5 mm²
Conductor cross sec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFKV 10/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.