

INDUSTRIAL COMPONENT DATA

HDFKV 25/Z 0714082 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFKV 25/Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFKV 25/Z
Catalog number	0714082
Category	Panel feed-through terminal block
Minimum order	25 Pcs
Document ID	EO-065B0D6A64
Generated	2026-08-01

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, charging current: 101 A, cross-section: 6 mm² - 35 mm², conductor connection direction with respect to the plug direction: -90 °, width: 15.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > PCB Connectors (PCC)
--------------	--

Additional Product Information

Key Commercial Data

Orderkey 0714082

Packing unit 25 pc

Minimum order quantity 25 pc

Note Made to Order (non-returnable)

Catalog page Page 632 (CC-2009)

GTIN 4046356180306

Weight per Piece (excluding packing) 70.590 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2
Nominal cross section 25 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 125 A
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 101 A
Maximum load current 125 A
Nominal voltage U_N 500 V
Open side panel No
Number of positions 1
Dimensions
Width 15.1 mm
Length 74.5 mm
Pitch 15.1 mm
Connection data
Note Terminal sleeve
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 6 mm²
Conductor cross section solid max. 35 mm²
Conductor cross section flexible min. 10 mm²
Conductor cross section flexible max. 25 mm²
Conductor cross section AWG min. 10
Conductor cross section AWG max. 2
Conductor cross section flexible, with ferrule without plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 25 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve max. 25 mm²
2 conductors with same cross section, solid min. 2.5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFKV 25/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.