

INDUSTRIAL COMPONENT DATA

HDFKV 4/Z 0714040 PHOENIX CONTACT Panel feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: HDFKV 4/Z



Manufacturer	PHOENIX CONTACT
MPN / Reference	HDFKV 4/Z
Catalog number	0714040
Category	Panel feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-80464BB82E
Generated	2026-08-01

Product Overview

Panel feed-through terminal block

Terminal block, connection type: Screw connection with traction capsule, Screw connection with traction capsule, number of poles: 1, charging current: 32 A, cross-section: 0.2 mm² - 6 mm², conductor connection direction with respect to the plug direction: -90 °, width: 8.1 mm

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > PCB Connectors (PCC)

Additional Product Information

Key Commercial Data

Orderkey 0714040

Packing unit 50 pc

Minimum order quantity 50 pc

Note Made to Order (non-returnable)

Catalog page Page 628 (CC-2009)

GTIN 4046356180153

Weight per Piece (excluding packing) 8.640 g

Custom tariff number 85369010

Country of origin GR (Greece)

General

Number of levels 1

Number of connections 2
Nominal cross section 4 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Maximum load current 41 A
Rated surge voltage 6 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Connection in acc. with standard IEC 60947-7-1
Nominal current I_N 32 A
Maximum load current 41 A
Nominal voltage UN 400 V (With metal panels of 1 mm ... 2.5 mm)
250 V (With metal panels over 2.5 mm ... 5 mm)
400 V (With plastic panels of 1 mm ... 4 mm)
Open side panel No
Number of positions 1
Dimensions
Width 8.1 mm
Length 39.5 mm
Pitch 8.1 mm
Connection data
Connection side Level 1 ext. 1
Connection method Screw connection
Conductor cross section solid min. 0.2 mm²
Conductor cross section solid max. 6 mm²
Conductor cross section flexible min. 0.2 mm²
Conductor cross section flexible max. 4 mm²
Conductor cross section AWG min. 24
Conductor cross section AWG max. 10
Conductor cross section flexible, with ferrule without plastic sleeve min. 0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max. 4 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min. 0.25 mm²
Conductor cross secti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / HDFKV 4/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.