

INDUSTRIAL COMPONENT DATA

MBK 2,5/E 1414006 PHOENIX CONTACT Mini feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: MBK 2,5/E



Manufacturer	PHOENIX CONTACT
MPN / Reference	MBK 2,5/E
Catalog number	1414006
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-796B393D7B
Generated	2026-08-02

Product Overview

Mini feed-through terminal block

Mini-terminal block, nominal voltage: 250 V, nominal current: 24 A, number of connections: 2, connection type: Screw connection, 1st floor, Dimensioning cross-section: 2.5 mm², cross-section: 0.2 mm² - 2.5 mm², installation class: NS 15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Key Commercial Data

Orderkey 1414006

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 516 (CL1-2011)

GTIN 4017918021269

Weight per Piece (excluding packing) 3.960 g

Custom tariff number 85369010

Country of origin IN (India)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 2.5 mm²

Color gray

Insulating material PA

Flammability rating according to UL 94 V2

Rated surge voltage 4 kV

Degree of pollution 3

Overvoltage category III

Insulating material group I

Maximum power dissipation for nominal condition 0.77 W

Maximum load current 24 A (with a 2.5 mm² conductor cross section)

Nominal current I_N 24 A

Nominal voltage U_N 250 V

Open side panel Yes

Shock protection test specification IEC 60529:2001-02

Back of the hand protection guaranteed

Finger protection guaranteed

Result of surge voltage test Test passed

Surge voltage test setpoint 4.8 kV

Result of power-frequency withstand voltage test Test passed

Power frequency withstand voltage setpoint 1.5 kV

Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed

Result of bending test Test passed

Bending test rotation speed 10 rpm

Bending test turns 135

Bending test conductor cross section/weight 0.2 mm² / 0.2 kg

2.5 mm² / 0.7 kg

Tensile test result Test passed

Conductor cross section tensile test 0.2 mm²

Tractive force setpoint 10 N

Conductor cross section tensile test 2.5 mm²

Tractive force setpoint 50 N

Result of tight fit on support Test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MBK 2,5/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.