

INDUSTRIAL COMPONENT DATA

MT 1,5 3100305 PHOENIX CONTACT Micro terminal

Brand: PHOENIX CONTACT | Manufacturer Part Number: MT 1,5



Manufacturer	PHOENIX CONTACT
MPN / Reference	MT 1,5
Catalog number	3100305
Category	Feed-through terminal block
Minimum order	50 Pcs
Document ID	EO-ABF46ECDE7
Generated	2026-08-02

Product Overview

Micro terminal

Microterminal, nominal voltage: 400 V, nominal current: 17.5 A, number of connections: 2, connection type: Screw connection, 1st floor, Dimensioning cross-section: 1.5 mm², cross-section: 0.14 mm² - 1.5 mm², mounting class: NS 15, colour: grey

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	PHOENIX CONTACT > Modular TBs
--------------	-------------------------------

Additional Product Information

Key Commercial Data

Orderkey 3100305

Packing unit 50 pc

Minimum order quantity 50 pc

Catalog page Page 523 (C-1-2017)

GTIN 4017918099251

Weight per Piece (excluding packing) 2.280 g

Custom tariff number 85369010

Country of origin TR (Turkey)

General

Number of levels 1

Number of connections 2

Potentials 1

Nominal cross section 1.5 mm²
Color gray
Insulating material PA
Flammability rating according to UL 94 V0
Rated surge voltage 4 kV
Degree of pollution 3
Overvoltage category III
Insulating material group I
Maximum power dissipation for nominal condition 0.56 W
Maximum load current 17.5 A (with 1.5 mm² conductor cross section)
Nominal current I_N 17.5 A
Nominal voltage U_N 400 V
Open side panel Yes
Shock protection test specification IEC 60529:2001-02
Back of the hand protection guaranteed
Finger protection guaranteed
Result of surge voltage test Test passed
Surge voltage test setpoint 4.8 kV
Result of power-frequency withstand voltage test Test passed
Power frequency withstand voltage setpoint 1.89 kV
Result of the test for mechanical stability of terminal points (5 x conductor connection) Test passed
Result of bending test Test passed
Bending test rotation speed 10 rpm
Bending test turns 135
Bending test conductor cross section/weight 0.14 mm² / 0.2 kg
0.5 mm² / 0.3 kg
1.5 mm² / 0.4 kg
Tensile test result Test passed
Conductor cross section tensile test 0.14 mm²
Tractive force setpoint 10 N
Conductor cross section tensile test 0.5 mm²
Tractive force setpoint 20 N
Conductor cr...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / MT 1.5 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.