


INDUSTRIAL COMPONENT DATA

PT 10 BU 3212123 PHOENIX CONTACT Feed-through terminal block

Brand: PHOENIX CONTACT | Manufacturer Part Number: PT 10 BU



Manufacturer	PHOENIX CONTACT
MPN / Reference	PT 10 BU
Catalog number	3212123
Category	Feed-through terminal block
Minimum order	1 Pcs
Document ID	EO-235AF98765
Generated	2026-08-01

Product Overview

Feed-through terminal block

Feed-through terminal, nominal voltage: 1000 V, nominal current: 57 A, number of connections: 2, connection type: Push-in connection, Dimensioning cross-section: 10 mm², cross-section: 0.5 mm² - 16 mm², installation class: NS 35/7.5, NS 35/15, colour: blue

Feed-through terminal block, nom. voltage: 1000 V, nominal current: 57 A, number of connections: 2, connection method: Push-in connection, Rated cross section: 10 mm², cross section: 0.5 mm² - 16 mm², mounting type: NS 35/7,5, NS 35/15, color: blue

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path PHOENIX CONTACT > Modular TBs

Additional Product Information

Technical dataProduct propertiesProduct type Feed-through terminal block

Area of application Railway industry

Machine building

Plant engineering

Number of connections 2

Number of rows 1

Potentials 1

Data management status

Article revision 09

Insulation characteristics

Overvoltage category III

Degree of pollution 3

Electrical properties Rated surge voltage 8 kV

Maximum power dissipation for nominal condition 1.82 W

Connection data Number of connections per level 2

Nominal cross section 10 mm²

Stripping length 18 mm ... 20 mm

Internal cylindrical gage A6

Connection in acc. with standard IEC 60947-7-1

Conductor cross section rigid 0.5 mm² ... 16 mm²

Cross section AWG 20 ... 6 (converted acc. to IEC)

Conductor cross section flexible 0.5 mm² ... 16 mm²

Conductor cross section, flexible [AWG] 20 ... 6 (converted acc. to IEC)

Conductor cross-section flexible (ferrule without plastic sleeve) 0.5 mm² ... 10 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 0.5 mm² ... 10 mm²

2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve 1.5 mm² ... 4 mm²

Nominal current 57 A

Maximum load current 70 A (with a 16 mm² conductor cross section, rigid)

Nominal voltage 1000 V

Nominal cross section 10 mm²

Connection cross sections directly pluggable

Conductor cross section rigid 1 mm² ... 16 mm²

Conductor cross-section flexible (ferrule without plastic sleeve) 4 mm² ... 10 mm²

Flexible conductor cross section (ferrule with plastic sleeve) 2.5 mm²

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send PHOENIX CONTACT / PT 10 BU with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.